

Environmental Protection Agency

§ 60.463

F = the proportion of total VOC's emitted by an affected facility that enters the control device (fraction).
G = volume-weighted average mass of VOC's in coatings consumed in a calendar month per unit volume of coating solids applied (kilograms per liter).
 L_c = the volume of each coating consumed, as received (liters).
 L_d = the volume of each VOC-solvent added to coatings (liters).
 L_r = the volume of VOC-solvent recovered by an emission control device (liters).
 L_s = the volume of coating solids consumed (liters).
 M_d = the mass of VOC-solvent added to coatings (kilograms).
 M_o = the mass of VOC's in coatings consumed, as received (kilograms).
 M_r = the mass of VOC's recovered by an emission control device (kilograms).
N = the volume-weighted average mass of VOC emissions to the atmosphere per unit volume of coating solids applied (kilograms per liter).
 Q_a = the volumetric flow rate of each gas stream leaving the control device and entering the atmosphere (dry standard cubic meters per hour).
 Q_b = the volumetric flow rate of each gas stream entering the control device (dry standard cubic meters per hour).
 Q_r = the volumetric flow rate of each gas stream emitted directly to the atmosphere (dry standard cubic meters per hour).
R = the overall VOC emission reduction achieved for an affected facility (fraction).
S = the calculated monthly allowable emission limit (kilograms of VOC per liter of coating solids applied).
 V_s = the proportion of solids in each coating, as received (fraction by volume).
 W_o = the proportion of VOC's in each coating, as received (fraction by weight).

§ 60.462 Standards for volatile organic compounds.

(a) On and after the date on which § 60.8 requires a performance test to be completed, each owner or operator subject to this subpart shall not cause to be discharged into the atmosphere more than:

(1) 0.28 kilogram VOC per liter (kg VOC/l) of coating solids applied for each calendar month for each affected facility that does not use an emission control device(s); or

(2) 0.14 kg VOC/l of coating solids applied for each calendar month for each affected facility that continuously uses an emission control device(s) operated

at the most recently demonstrated overall efficiency; or

(3) 10 percent of the VOC's applied for each calendar month (90 percent emission reduction) for each affected facility that continuously uses an emission control device(s) operated at the most recently demonstrated overall efficiency; or

(4) A value between 0.14 (or a 90-percent emission reduction) and 0.28 kg VOC/l of coating solids applied for each calendar month for each affected facility that intermittently uses an emission control device operated at the most recently demonstrated overall efficiency.

§ 60.463 Performance test and compliance provisions.

(a) Section 60.8(d) and (f) do not apply to the performance test.

(b) The owner or operator of an affected facility shall conduct an initial performance test as required under § 60.8(a) and thereafter a performance test for each calendar month for each affected facility according to the procedures in this section.

(c) The owner or operator shall use the following procedures for determining monthly volume-weighted average emissions of VOC's in kg/l of coating solids applied.

(1) An owner or operator shall use the following procedures for each affected facility that does not use a capture system and control device to comply with the emission limit specified under § 60.462(a)(1). The owner or operator shall determine the composition of the coatings by formulation data supplied by the manufacturer of the coating or by an analysis of each coating, as received, using Method 24. The Administrator may require the owner or operator who uses formulation data supplied by the manufacturer of the coatings to determine the VOC content of coatings using Method 24 or an equivalent or alternative method. The owner or operator shall determine the volume of coating and the mass of VOC-solvent added to coatings from company records on a monthly basis. If a common coating distribution system serves more than one affected facility or